



NOTE: THIS SKETCH IS A NON-PROPRIETARY GRAPHIC REPRESENTATION OF A LUMINAIRE THAT MAY MEET THE SPECIFICATION REQUIREMENTS. IT IS NOT INTENDED TO INDICATE A CERTAIN MANUFACTURER OR PREFERENCE.

#### LUMINAIRE REQUIREMENTS:

1. HOUSING – COLD ROLLED STEEL OR EXTRUDED ALUMINUM BODY WITH STAINLESS STEEL HARDWARE. SIZE AS INDICATED IN LUMINAIRE SCHEDULE.
2. OPTICS – REFRACTIVE LENS OPTIMIZED FOR ASYMMETRIC DISTRIBUTION.
3. LIGHT SOURCE – SOLID STATE LEDS, 3500K CCT UON, MINIMUM 80 CRI UON, AND MINIMUM EFFICACY OF 70 LUMENS/WATT UON. INITIAL LUMEN OUTPUT AS INDICATED IN LUMINAIRE SCHEDULE.
4. DRIVER – REPLACEABLE, INTEGRAL, HIGH-EFFICIENCY DIMMABLE DRIVER WITH MINIMUM 0.9 PF, OPERATING VOLTAGE OF 120–277V, THERMAL MANAGEMENT, AND < 20% THD. ON/OFF CONTROL AND FULLY DIMMABLE DOWN TO 10% MINIMUM OR AS INDICATED IN LUMINAIRE SCHEDULE.
5. CERTIFICATION – UL LISTED FOR DRY LOCATION, ROHS COMPLIANT. COMPLIES WITH IES LM79, LM80 AND TM21 TESTING STANDARDS.
6. MOUNTING – RECESSED IN HARD OR ACOUSTICAL TILE CEILING.
7. OPTIONS – VARIOUS PROFILE DIMENSIONS AND RUN LENGTHS.

## RECESSED LINEAR WALL WASH

REVISED:

NOVEMBER 2020

LIGHTING PLATE:

NL-9